

Chemistry and Technology of Fuels and Oils

6⁽⁶⁴⁶⁾'2024

Head Editor

B. P. Tumanyan – Dr. Eng. Sci., prof.

Editorial Board

I. A. Arutyunov – Dr. Eng. Sci., prof.

S. N. Volgin – Dr. Eng. Sci., prof.

I. B. Grudnikov – Dr. Eng. Sci., prof.

V. L. Lashkhi – Dr. Eng. Sci., prof.

A. Luksa – Dr. Eng. Sci., prof. (Poland)

A. M. Mazgarov – Dr. Eng. Sci., prof.

K. B. Rudyak – Dr. Eng. Sci., prof.

E. P. Seregin – Dr. Eng. Sci., prof.

Sun Tengfei – prof. (China)

Publisher— ICST «TUMA Group» LLC

Редактор

В. С. Дмитриева

Ответственный секретарь

О. В. Любименко

Графика и верстка

В. В. Земсков

Подготовка материалов

С. О. Бороздин,

А. Д. Остудин,

В. Ю. Попова

Адрес редакции:

105318, г. Москва,

Измайловское шоссе, д. 20-1Н

e-mail: httm@list.ru

Материалы авторов не возвращаются.

Редакция не несет ответственности за достоверность информации в материалах, в том числе рекламных, предоставленных авторами для публикации.

Формат 60 × 84 1/8.

Печать офсетная.

Усл. печ. л. 7.

Тираж 1000 экз.

Отпечатано в ООО ИПФ «СТРИНГ»
424006, Республика Марий Эл,
г. Йошкар-Ола, ул. Строителей, 95

Contents

<i>A. V. Ulitko, Yu. M. Pimenov.</i> Chemotology Problematic Aspects and Development Lines of Research and Testing System	13
<i>K. V. Shatalov, S. N. Volgin.</i> Methods for Assessing Propensity to Deposit and Storage Ability of Aviation Turbine Fuels	22
<i>G. M. Balak, S. N. Volgin, K. N. Melentsov.</i> Quick Determination of Biodiesel Impurities in Hydrocarbon Fuels by Thin-Layer Chromatography Method	31
<i>P. A. Strizhak, D. V. Antonov, S. M. Aldoshin, L. S. Yanovsky.</i> New Generation Liquid Synthetic Fuels	56
INNOVATIVE TECHNOLOGIES OF OIL AND GAS	
<i>Tao Lin, Jin Nan, Li Zhuangwei, Yang Baojian, Ma Hongwei, Li Qianyu, Wen Zhiliang, Ren Laiao.</i> Simulation Analysis of Contact Stress Variation of PDC Tooth Surface at Different Rotational Speeds	65
<i>Shengli Gong, Cheng Liu, Changlin Shi.</i> Quantitative Evaluation of Tight Shale's Pore Configuration: Mathematics and Experiments	73
<i>Shun Guo, Chao Gao, Chao Ding, Jintao Yin, Yanping Lu, Zhanhong Qian, Cheng Huang.</i> Experimental Study on the Characteristics and Diagenetic Processes of Typical Tight Oil Reservoirs	81
<i>Kai Wang, Hongxia Guo, Pingdong Li, Chunlin Liu, Zhicheng Yang, Ke Liu, Shengjun Han, Haizhou He.</i> Sedimentary Microphase Characterization of Sandstone Reservoirs and Analysis of Reservoir Physical Properties	90
<i>Bei Liu, Jiliang Zhang, Dong Wang, Xiong Zhang, Pengju Gao.</i> Exploration and Practice of Geological Drilling Technology in the Field of Oil and Gas	101
<i>Pengju Gao, Jiliang Zhang, Peng Chang, Xiaolong Wu, Bei Liu.</i> Key Drilling Technology of Well in Exploration Block	105
<i>Zhang Weiguo, Gao Deli, Yan De, Zeng Yijin, Wen Zhiliang.</i> Effect of Continuous Circulation Technology on Cutting Bed in Extended-Reach Drilling	110
<i>Baisong Tang, Shuo Feng, Jie Zhao, Jianhong Chen, Donghong Guo, Yufeng Wang.</i> Study on ECD during the Construction of Extended Reach Wells	117
<i>Yang Zhao, Anning Zhou, Ruichen Ren, Wenge Song, Jianmin Li, Wei Zhao, Jinzhou Qu, Tianhao Nan, Chao Niu, Zhihao Guan.</i> Research on Desliming Pretreatment and Electroflocculation Settlement Process of High Ash Coal Slurry Water and Oily Wastewater	126
<i>Jianwei Fu, Mengling Chen, Liangyu Chen, Rongbo Shao, Yonggui Li, Zhi Chen, Jintao Xin, Yi Pan.</i> Reservoir Permeability Prediction Method Based on Fuzzy Clustering and Machine Learning	137
<i>Wei Guo, Yuan Cai, Weiwei Dong, Ning Wang, Hairong Zhang, Yun Mo.</i> Research on the Management Method of New Integrated Energy System Considering Carbon Emission Reduction	144
<i>Wang Shuai.</i> Experimental Study on CO ₂ Injection to Enhance Recovery and Its Storage Characteristics in Low Permeability Gas Reservoirs	153
<i>Jun Ni, Chengjun Wang, Hailong Dang, Hongwei Jing.</i> Influence of Asphaltene Precipitation during CCUS Processes in Oil Reservoirs on Enhancing Recovery Rates	159
<i>Wei Wu, Nan Zhou, Xiaohua Zhu, Mingwang Bai.</i> Research on the Rock Pore Structure and Porosity-Permeability Characteristics of Oilfield Saline Aquifer CCS	165
<i>Mingwei Ren, Yunbo Chen, Kewei Gao, Zheng Wang, Qian Ma, Lianying Liu.</i> In-situ Growing Polymer Particles on Carbon Fiber for Improving Interfacial Properties of Epoxy Composites	171

<i>Yun Jianbing, Yuan Kaitao, Li Changyan, Luo Xin, Wang Yaya, Yang Mingkun, Zhou Xiao, Wang Jing.</i> Analysis of Gas Reservoir Types and Main Controlling Factors of Enrichment and High Yield in Sichuan Basin	180
<i>Bai Xingjia, Feng Rong, Zhang Zhehao, Xu Jing, Wang Junjun, Bai Yiyuan, Yang Wenlai, Li Yuanjun.</i> Study on Gas Production Mechanism of Foam Drainage and Optimization of Technological Parameters	187
<i>Liu Ting, Zhang Zheng, Dongye Shengfu, Zhao Jinlin, Zhang Fashi, Yu Yao.</i> Evaluation of Chemical Properties of Microemulsion and Experimental Study of Oil Displacement Mechanism	194
<i>Jiang Jun.</i> Chemical Performance Evaluation and Economic Benefit Analysis of Corrosion Resistant Coatings for Oil and Gas Pipelines	202

А. В. Улитко, Ю. М. Пименов

ФАУ «25 ГосНИИ химмотологии Минобороны России»

25gosnihim@mil.ru

Проблемы и направления развития системы исследований и испытаний в химмотологии

Дана характеристика противоречий, сопровождающих на современном этапе развитие системы исследований (испытаний) и оценки соответствия горюче-смазочных материалов (ГСМ) требованиям техники. Предложены направления и отдельные примеры научно-технических решений, демонстрирующие возможности повышения эффективности исследований (испытаний), на основе совершенствования методологии моделирования химмотологических процессов и прогнозирования эксплуатационных свойств перспективных ГСМ для их ускоренной разработки, оценки соответствия и внедрения в технику.

Ключевые слова: горюче-смазочные материалы, эксплуатационное свойство, химмотологический процесс, моделирование, определяющие факторы, информативность, интегральная оценка, прогнозирование, принятие решений.

DOI: 10.32935/0023-1169-2024-646-6-13-21

A. V. Ulitko, Yu. M. Pimenov.

The 25-th State Research Institute of Chemmotology, Ministry of Defense of the Russian Federation

Chemmotology Problematic Aspects and Development Lines of Research and Testing System

The characteristics of contradictions following at the present stage the development of system for research (testing) and compliance assessment of fuels and lubricants (FL) meeting the technical requirements have been provided. There were proposed the lines and individual examples of scientific and technical solutions, demonstrating opportunities to increase the efficiency of research (testing) based on improving the methodology for simulation of chemmotology processes and operational properties' forecasting for the perspective fuels and lubricants so that to push on their development, compliance assessment and insertion into equipment.

Key words: fuel and lubrication materials, operational property, chemmotology process, simulation, determining factors, informative content, integral assessment, forecasting, decision making.

К. В. Шаталов, С. Н. Волгин

ФАУ «25 ГосНИИ химмотологии Минобороны России»

25gosnii_16nio@mil.ru

Методы оценки склонности к образованию отложений и сохраняемости топлив для реактивных двигателей

Представлено краткое описание методов исследования термоокислительных превращений топлив для реактивных двигателей, протекающих при их применении. Методы оценки

термоокислительной стабильности в динамических условиях и склонности к образованию отложений моделируют различные процессы образования отложений в топливной системе газотурбинного двигателя. Метод оценки химической стабильности позволяет исследовать жидкофазное окисление при хранении топлива в резервуарах.

Ключевые слова: топлива для реактивных двигателей, склонность к образованию отложений, сохраняемость,

термоокислительная стабильность, химическая стабильность, метод испытания.

DOI: 10.32935/0023-1169-2024-646-6-22-30

K. V. Shatalov, S. N. Volgin.

The 25-th State Research Institute of Chemmotology, Ministry of Defense of the Russian Federation

Methods for Assessing Propensity to Deposit and Storage Ability of Aviation Turbine Fuels

A brief description of a set of methods aimed at a comprehensive assessment of the propensity of aviation turbine fuels to deposit formation is presented. Methods for assessing thermal oxidative stability under dynamic conditions and the tendency to deposit formation simulate various conditions for the formation of deposits in the fuel system of a gas turbine engine. The chemical stability assessment method simulates the conditions of liquid-phase oxidation during fuel storage in tanks.

Key words: aviation turbine fuels, deposition tendency, oxidation stability, chemical stability, test method.

Г. М. Балак, С. Н. Волгин, К. Н. Меленцов

ФАУ «25 ГосНИИ химмотологии Минобороны России»

25gosniihim@mil.ru

Оперативное определение примесей биодизельных топлив в углеводородных топливах методом тонкослойной хроматографии

Представлен метод оперативного детектирования и определения содержания примесей биодизельных топлив различного происхождения в углеводородных топливах различных групп (подгрупп). Метод основан на разделении компонентов анализируемых проб в тонком слое сорбента на пластинах для тонкослойной хроматографии при элюировании смесями полярного и неполярных растворителей. Детектирование концентраций биодизельных топлив проводят обработкой пластины с хроматограммой смесью растворов соединений железа. С учетом простоты выполнения аналитических операций и отсутствия необходимости использования сложного аналитического оборудования метод может быть рекомендован к применению как в стационарных лабораториях, так и во внелaboratorных условиях.

Ключевые слова: биодизельные топлива, углеводородные топлива, тонкослойная хроматография, детектирование, количественное определение.

DOI: 10.32935/0023-1169-2024-646-6-31-39

G. M. Balak, S. N. Volgin, K. N. Melentsov.

The 25-th State Research Institute of Chemmotology, Ministry of Defense of the Russian Federation

Quick Determination of Biodiesel Impurities in Hydrocarbon Fuels

by Thin-Layer Chromatography Method

A method used for quick detection and determination of the impurities' content in biodiesel fuels (BF) of various origins in hydrocarbon fuels of various groups (subgroups) has been presented. The method is based on the separation of the analyzed samples' components in a thin layer of sorbent on plates for thin-layer chromatography during elution with mixtures of polar and non-polar solvents. BF detection is carried out by treating a plate with a chromatogram with a mixture of solutions containing iron salts. The range of determined BF concentrations is from 0.1 to 100% vol., the relative standard deviation of the determination results is from 0.07 to 0.2. Considering that performing analytical operations is simple and the need to use complicated analytical equipment is absent, the method can be recommended for application both in stationary laboratories and in non-laboratory conditions.

Key words: *biodiesel, hydrocarbon fuels, thin layer chromatography, detection, quantitative determination.*

П. А. Стрижак¹, Д. В. Антонов¹, С. М. Алдошин², Л. С. Яновский^{2,3}

¹Национальный исследовательский Томский политехнический университет,

²Федеральный исследовательский центр проблем химической физики
и медицинской химии, г. Черноголовка,

³Центральный институт авиационного моторостроения им. П. И. Баранова, г. Москва,
pavelspa@tpu.ru

Химмотология жидких синтетических топлив нового поколения

Проанализированы современные достижения отечественной науки в области разработки синтетических топлив назначения. Представлено сравнение наработок с мировыми аналогами. Выделены перспективное сырье и технологии синтеза топливных композиций. Сформулированы основные требования к соответствующим топливам, перечень контролируемых свойств и характеристик полного жизненного цикла: приготовление, хранение, транспортировка, распыление, горение, нейтрализация антропогенных выбросов. Определены рациональные методики и этапы тестирования топлив нового поколения с учетом ограниченных объемов производства. Сформулированы рекомендации по совершенствованию системы научно-исследовательских и опытно-конструкторских работ с целью получения синтетических жидких топлив.

Ключевые слова: синтетические жидкие топлива, авиационное топливо, биотопливо, полный жизненный цикл.

DOI: 10.32935/0023-1169-2024-646-6-56-64

P. A. Strizhak¹, D. V. Antonov¹, S. M. Aldoshin¹, L. S. Yanovsky^{2,3}

¹National Research Tomsk Polytechnic University, Tomsk

²Federal Research Center of Problems of Chemical Physics and Medicinal Chemistry RAS,
Chernogolovka

³Baranov Central Institute of Aviation Motor Development, Moscow

New Generation Liquid Synthetic Fuels

The paper analyzes modern achievements of domestic science in the synthetic fuels development. A comparison of world analogues is presented. Promising raw materials and technologies for the synthesis of fuel compositions are identified. The main requirements for the corresponding fuels, a list of controlled properties and characteristics of the full life cycle are formulated: preparation, storage, transportation, spraying, combustion, neutralization of anthropogenic emissions. Rational methods and stages of testing new generation fuels are determined taking into account limited production volumes. Recommendations are formulated for improving the system of research and development work in order to obtain synthetic liquid fuels.

Key words: *synthetic liquid fuels, aviation fuel, biofuels, full life cycle, testing.*

Tao Lin¹, Jin Nan¹, Li Zhuangwei¹, Yang Baojian¹, Ma Hongwei¹, Li Qianyu²✉, Wen Zhiliang²,

Ren Laiao²

¹ Tianjin Branch of CNOOC Ltd., Tianjin, China;

² China University of Petroleum in Beijing, Changping District, Beijing, China.

13085145210@163.com

Simulation Analysis of Contact Stress Variation

of PDC Tooth Surface at Different Rotational Speeds

When drilling in deep hard-rock formation, polycrystalline diamond compact (PDC) drill bit has the phenomenon of fracture of PDC tooth due to high stress on tooth surface, while the current research on PDC tooth breaking focuses on the efficiency of PDC tooth breaking, and less on the change of contact stress on tooth surface when breaking rock. The rotational speed is an important mechanical parameter in oil drilling operation, in order to deeply study the influence of rotational speed on the contact stress of the tooth surface when PDC tooth breaks the rock, we established the PDC single-tooth rock-breaking model, investigated the rock-breaking process of the PDC tooth under different rotational speeds, and analyzed the change of the stresses of the rock and the PDC tooth when the PDC tooth breaks the rock. The results show that in the process of rock cutting by PDC teeth, the destruction of rock is gradual, the size and position of the contact surface between rock section and PDC teeth change constantly, resulting in the existence of stress concentration and impact on the surface of PDC teeth, the maximum value of the stress can reach 1194 MPa when the rotational speed is 100 RMP, and as the rotational speed increases, the speed of rock being broken is accelerated, and when the rotational speed is greater than 90 RMP, the The increase of rotational speed will cause more

violent impact creation on the PDC teeth when breaking the rock, which is not favorable to the service life of the drill bit. The relevant findings can help to reveal the intermediate damage mechanism of PDC teeth under different rotational speeds when drilling in deep hard-rock formations and provide a reference for the scientific selection of rotational speeds.

Keywords: *rotational speed, hard rock formation, PDC cutter teeth, rock-breaking stress, drill bit longevity.*

Shengli Gong^{1,2,3}, Cheng Liu^{1,2,3}✉, Changlin Shi^{1,2,3}

¹ CNOOC EnerTech-Drilling & Production Co., Tianjin, China;

² CNOOC Energy Technology & Services Limited Key Laboratory for Exploration & Development of Unconventional Resources, Tianjin, China;

³ National Engineering Research Center of Offshore Oil and Gas Exploration, Beijing, China.

chenxxqc5238@126.com

Quantitative Evaluation of Tight Shale's Pore Configuration:

Mathematics and Experiments

The pore configuration of shale has always been a contentious topic in shale gas exploration research due to its complexity, aperture size and dispersion varies from nanometers to millimeters. To investigate the pore configuration of shale, this study selected the Longmaxi Formation shale in the Sichuan Basin as the research subject and conducted high-pressure mercury, cryogenic liquid nitrogen and cryogenic carbon dioxide adsorption experiments. By employing a combination of characterization methods and fractal dimension analysis, the study delved deeply into the nano-level pore features of the Longmaxi Formation shale. The experimental results demonstrated that the pores of the Longmaxi Formation shale samples could be classified into three types, of which the first and second types indicated good pore connectivity, while the third type showed poor connectivity. Moreover, the capacity and particular surface area of the minuscule pores were predominantly distributed at pore sizes of 0.3~0.5 nm. Additionally, mesopores could provide a substantial amount of pore volume, while micropores played a crucial role in controlling the total specific surface area and serving as the key location for gas adsorption and storage. Furthermore, the pore configuration of the Longmaxi Formation shale adhered to fractal laws, and the fractal dimension of pores larger than 50 nm was 2.9176, indicating that larger pores were more complex than medium and small pores. In conclusion, this study offered valuable insights into the pore architecture of the Longmaxi Formation shale and underscored the significance of considering pore configuration in shale gas exploration.

Keywords: *tight shale, nanopores, fractal theory, microstructure.*

**Shun Guo^{1,2,3}, Chao Gao^{1,2,3}✉, Chao Ding^{4,5}, Jintao Yin^{1,2,3}, Yanping Lu^{6,7}, Zhanhong Qian^{6,7},
Cheng Huang^{2,8}**

¹ Shaanxi Yanchang Petroleum (Group) Corp. Ltd., Xi'an, China;

² Shaanxi Key Laboratory of Carbon Dioxide Sequestration and Enhanced Oil Recovery, Xi'an, China;

³ Shaanxi Key Laboratory of Lacustrine Shale Gas Accumulation and Exploitation, Xi'an, China;

⁴ School of Earth Sciences and Engineering, Xi'an Shiyou University, Xi'an, China;

⁵ Provincial Key Lab of Hydrocarbon Accumulation Geology, Xi'an Shiyou University, Xi'an, China;

⁶ Qinghai Province Key Laboratory of Oil and Gas Geology of Plateau Saline Lake Basin, Dunhuang, China;

⁷ Research Institute of Exploration & Development, PetroChina Qinghai Oilfield Company, Dunhuang, China;

⁸ School of Chemical Engineering, Northwest University, Xi'an Shaanxi, China.

gaonan89358240@163.com

Experimental Study on the Characteristics and Diagenetic Processes of Typical Tight Oil Reservoirs

The southern part of the Ordos Basin, in the Fuxian area, where the Yanchang Formation's Chang 7 Member is a new stratigraphic unit for tight oil development, and there has been little research on its pore structure and diagenetic processes. This paper takes the Chang 7 Member in the Fuxian area as an example and systematically conducted a micro-scale reservoir property study of the Chang 7 tight oil using a large number of thin sections, scanning electron microscopy, physical properties, and CT scanning experiments. The results show that the sandstone types in the Chang 7 Member of the study area are mainly lithic arkose, followed by lithic arkose and sublithic arkose. The quartz content in the Chang 7 Member sandstones is relatively high, ranging from 15% to 47%, with an average of 31%. The types of pores developed include intergranular pores, intercrystalline pores, intragranular dissolution pores, intergranular dissolution pores, organic matter pores, and micro-fractures. Compaction, cementation (silica cementation, carbonate cementation, clay mineral cementation), and metasomatism have a destructive effect on reservoir quality; constructive diagenetic processes mainly include chlorite cementation and dissolution. Diagenetic sequence analysis indicates that the Ro value of the Chang 7 Member in the study area is between 0.79-0.91%, belonging to the late diagenetic stage A period. Early calcite is mostly pore-filling, and late calcite precipitates to fill dissolution pores. Clay minerals are mainly illite-smectite mixed layers, with the content of smectite in the mixed layers being less than 41%, and some less than 15%.

Keywords: Ordos Basin, Chang 7 Member, tight oil reservoir, pore structure, diagenetic processes.

Kai Wang¹✉, Hongxia Guo², Pingdong Li¹, Chunlin Liu¹, Zhicheng Yang¹, Ke Liu¹, Shengjun Han¹, Haizhou He¹

¹ PetroChina Changqing Oilfield Company, Xi'an, Shanxi, China;

² ShaanXi HaoShou Energy Technology Co., Ltd, Xi'an, Shanxi, China.

986182354@qq.com

Sedimentary Microphase Characterization of Sandstone Reservoirs and Analysis of Reservoir Physical Properties

This paper takes the Chang8 reservoir of Yanchang Group in Yanchi area as the research object, aiming at revealing its sedimentary microphase and reservoir characteristics, and providing scientific basis for oil and gas exploration and development. The distribution characteristics of the sedimentary microphase and the physical characteristics of the reservoir are systematically studied by using field geological profile, drilling core, well logging and experimental analysis. The results show that the sedimentary microphase of the reservoir of Long 8 Formation Group mainly includes submerged diversion channel, submerged natural dyke and diversion interbay, etc. The average thickness of seepage sand layer of submerged diversion channel phase is 20.3 m, and the average value of sand-ground ratio is 0.53, among which, the type of sand formation of the submerged diversion channel phase is a double-segment II type curve characterized by the combination of heavy jumping component and fine-grained suspended component, showing good pore connectivity. In terms of reservoir characteristics, the Chang8 oil formation shows low porosity (10.83% on average) and extra-low to ultra-low permeability ($0.776 \cdot 10^{-3} \mu\text{m}^2$ on average), with intergranular pores and feldspathic pores dominating the pore structure, and feldspathic pores accounting for 55.42% of the total pores, and there are a small number of clastic pores, intergranular pores, intergranular pores, and microcracks, which reflect the influence of diagenesis on the reservoir material. These characteristics reflect the significant influence of diagenesis on the physical properties of the reservoir. This study provides an important geological basis for the exploration and development of Yanchi Yanchang Group Long 8 reservoir, and helps to optimize the reservoir development plan and improve the recovery rate.

Keywords: Yanchi area, Yanchang Formation Long 8 reservoir, sedimentary microphase, reservoir characterization; diagenesis.

Bei Liu^{1,2}, Jiliang Zhang³, Dong Wang⁴, Xiong Zhang^{1,2}, Pengju Gao⁵✉

¹ Xi'an Center of Mineral Resources Survey, China Geological Survey, Xi'an Shaanxi, China;

² Technology Innovation Center for Gold Ore Exploration, Xi'an Center of Mineral Resources Survey, China Geological Survey, Xi'an, Shaanxi, China;

³ Fifth Prospecting Team of Shandong Coal Geology Bureau, Jinan, Shandong, China;

⁴ Directional Drilling Company, BHDC, CNPC, Tianjin, China;

⁵ Institute of Exploration Techniques, CAGS, Langfang Hebei, China.

pengjgao@163.com

**Exploration and Practice of Geological Drilling Technology
in the Field of Oil and Gas**

In recent years, the domestic geological prospecting field attaches great importance to and promotes green exploration work, and strengthening the research on green exploration technology and methods is the target requirement for the healthy and sustainable development of geological prospecting work in the field of oil and gas. In this paper, green drilling work carried out in typical geological landscape areas of northwest China is studied, drilling equipment is selected scientifically according to local conditions, and drilling engineering technology and methods are studied, including implementing drilling methods of “multi-holes from one position” and “drilling instead of trenching”, innovating drilling technology, optimizing coring bit and applying environment-friendly flushing fluid, etc., site control and protection are strengthened during construction, environmental recovery and treatment are implemented after construction, production guarantee measures for green drilling construction are explored, effectively reducing the intensity of environmental damage caused by engineering activities and the cost of environmental recovery and treatment, Drilling work has achieved the goal of improving quality and increasing efficiency, and achieved a win-win situation in economic benefits and environmental protection.

Keywords: *green exploration, oil and gas, portable full hydraulic rig, drilling technology, northwest China, geological landscape.*

Pengju Gao¹, Jiliang Zhang², Peng Chang⁵, Xiaolong Wu¹, Bei Liu^{3,4}✉

¹ Institute of Exploration Techniques, CAGS, Langfang Hebei, China;

² Fifth Prospecting Team of Shandong Coal Geology Bureau, Jinan, Shandong, China;

³ Xi'an Center of Mineral Resources Survey, China Geological Survey, Xi'an Shaanxi, China;

⁴ Technology Innovation Center for Gold Ore Exploration, Xi'an Center of Mineral Resources Survey, China Geological Survey, Xi'an Shaanxi, China;

⁵ Gas Production Plant 5 of PetroChina Changqing Oilfield Company, CNPC, Ordos, China.

lbeiliubei@163.com

Key Drilling Technology of Well in Exploration Block

In order to serve the gas clean energy exploration in Beijing, Tianjin and Hebei, Institute of Exploration Techniques (CAS) undertook the drilling task of gas exploration well D22 in Xiong'An New Area. This paper analyzes the engineering situation and construction difficulties of well D22, and introduces the drilling technology of each drilling operation. In the construction process, according to the characteristics of dolomite thermal reservoir, bit optimization, coring technology, plugging technology and borehole trajectory control technology are studied.

Keywords: *Xiong'an New Area, gas drilling, coring, plugging, directional drilling.*

Zhang Weiguo^{1,2}, Gao Deli¹, Yan De²✉, Zeng Yijin^{1,3}, Wen Zhiliang¹

¹ China University of Petroleum (Beijing), Beijing, China;

² CNOOC China Ltd Shenzhen Branch, Guangdong, China;

³ SINOPEC Research Institute of Petroleum Engineering Co. Ltd, Beijing, China.

yande@cnooc.com.cn

Effect Ofcontinuous Circulation Technology on Cutting Bed in Extended-Reach Drilling

Continuous circulation technology can realize the continuous circulation of continuous pumping during drilling, which can be used to improve borehole cleanliness in extended-reach drilling and prevent cutting bed accumulation from adversely affecting downhole operations. This paper describes the mechanism of continuous circulation technology and the advantages and disadvantages of its supporting equipment, analyzes the theoretical model of cutting bed migration in extended-reach drilling, studies the distribution, thickness and migration law of cutting bed when continuous circulation technology is used, and optimizes and recommends the flowrate, ROP and drillstring rotation speed of well Panyu A in eastern part of the South China Sea. The results show that the cutting bed of the extended-reach drilling has wavy distribution and dynamic migration with time, and the migration velocity of the cutting bed is inversely proportional to the hole size. The migration direction is from the bottom of the well to the head of the well. The thickness of the cutting bed is the largest at the beginning of the horizontal section, and the thickness near the bottom of the well is the smallest. The research results provide a theoretical reference for borehole cleaning control in extended-reach well.

Keywords: *extended-reach drilling, continuous circulation technology; cutting bed, borehole cleaning, drilling parameter.*

Baisong Tang¹, Shuo Feng¹, Jie Zhao¹, Jianhong Chen¹, Donghong Guo², Yufeng Wang³✉

¹ CNOOC China Limited, Tianjin Branch, China;

² CNOOC EnerTech-Drilling & Production Co., China;

³ China University of Petroleum-Beijing, China.

beijingwyf@126.com

Study on ECD During the Construction of Extended Reach Wells

The vertical depth and horizontal length of extended reach wells vary greatly, leading to significant pressure losses along the wellbore. Improper downhole pressure control during drilling, tripping, casing running, cementing, and completion operations can result in wellbore collapse, well instability, and other related issues. By researching the downhole ECD model during well construction, the ECD calculation methods were established, which was suitable for drilling, tripping, casing running, cementing, and gravel packing operations. The computation of ECD data across diverse operational scenarios, when coupled with the analysis of three pressure profiles, enables the precise identification of potential hazards for each operation. By implementing suitable mitigation measures, the risks associated with these operations can be significantly reduced. Utilizing an extended reach well as a case study, this paper aims to provide a comprehensive analysis of the process of identifying and

mitigating risks through ECD data across various operations. The insights gained from this study will serve as a valuable resource for similar extended reach well projects.

Keywords: *extended reach well, ECD, three pressure profile, drilling, cementing, completion.*

**Yang Zhao^{1,2}, Anning Zhou¹, Ruichen Ren³, Wenge Song², Jianmin Li¹, Wei Zhao¹,
Jinzhou Qu¹, Tianhao Nan¹✉, Chao Niu², Zhihao Guan²**

¹ College of Chemistry and Chemical Engineering, Xi'an University of Science and Technology, Xi'an, China;

² Coal Processing Center, CHN Enegy Shendong Coal Group Co., Ltd., Yulin, China;

³ Fuxin Technical University Mineral processing and using Science and Technology Co.,Ltd, China.
ss1560810@126.com

Research on Desliming Pretreatment and Electroflocculation Settlement Process of High Ash Coal Slurry Water and Oily Wastewater

In this study, the treatment method of high ash coal mud water and oily wastewater was systematically optimized by combining desliming pretreatment with electroflocculation and sedimentation process. The experiments used gravity settling method for desliming pretreatment and combined with electroflocculation settling process under different settling time, temperature and current density conditions, respectively. The results showed that after the desliming pretreatment, the concentration of suspended solids in the coal slurry water and the oily wastewater was reduced, and the removal rates reached 59.1% and 55.6%, respectively. Under the conditions of electroflocculation treatment with a current density of 3 mA/cm² and a treatment time of 20 min, the suspended solids concentrations of coal slurry water and oily wastewater were further reduced to 200.8 mg/L and 230.1 mg/L with removal rates of 61.0% and 48.9%, respectively. After the application of the combined process, the suspended solids removal rate of coal slurry water and oily wastewater increased to 71.4% and 68.5%, respectively, and the concentration of suspended solids decreased to 145.8 mg/L and 170.2 mg/L, respectively. With regard to the comprehensive indexes of water quality, the combined process significantly reduced the turbidity of coal slurry water and oily wastewater from 314.5 NTU and 344.4 NTU to 90.7 NTU and 105.8 NTU, respectively; electrical conductivity and conductivity of coal slurry water and oil wastewater were further decreased to 200.8 mg/L and 230.1 mg/L, respectively; the removal rate was 61% and 48.9%, respectively. 105.8 NTU; conductivity decreased from 1238.1 μS/cm and 1343.2 μS/cm to 1120.4 μS/cm and 1215.9 μS/cm, respectively; and pH remained relatively stable with small changes. This study provides a set of efficient, low-cost and environmentally friendly treatment technology for coal and oil industries, which significantly improves the production efficiency and product quality of coal preparation plants and oil fields, and has important practical application value.

Keywords: *high ash coal slurry water, oily wastewater, desliming pretreatment, electroflocculation and sedimentation, water quality improvement, suspended solids removal rate.*

Jianwei Fu¹✉, Mengling Chen¹, Liangyu Chen², Rongbo Shao¹, Yonggui Li², Zhi Chen², Jintao Xin³, Yi Pan³

¹ State Key Laboratory of Petroleum Resources and Engineering, China University of Petroleum (Beijing), Beijing, China;

² International Branch, China National Logging Corporation, Beijing, China;

³ College of Oil and Gas Engineering, Liaoning Petrochemical University, Fushun, Liaoning, China.
cups20012006@163.com

Reservoir Permeability Prediction Method Based on Fuzzy Clustering and Machine Learning

With the in-depth development of oil and gas exploration technology and the development of low permeability reservoirs, the permeability prediction method represented by machine learning technology has been widely applied. However, it is limited by data distribution, data heterogeneity, and model complexity. Traditional machine learning methods are not accurate, and the results are not stable when predicting permeability. Aiming at some problems encountered by traditional machine learning algorithms in predicting permeability, this paper takes carbonate rocks in Region X as the research object, comprehensively analyzes the geological characteristics of carbonate rocks, analyzes the importance of input features by XGBoost built-in module, and selects seven logging curves as the inputs of the network model combined with actual conditions. A Fuzzy C-means algorithm based on fuzzy logic is used to cluster the data. According to the clustering results, the data is divided into several subsets, and the SVR or LSTM model is trained for each subset. The predictions of all subsets are then combined to get the final prediction. The performance of the model is evaluated using evaluation indicators (such as mean square error, determination coefficient) and compared with direct prediction methods without clustering. The results show that the coefficient of determination (R^2) of prediction after FCM clustering reaches 0.86, and the average absolute error is 0.068. The determination coefficients (R^2) of LSTM and SVR algorithms for direct prediction are 0.75 and 0.73, respectively. It is proved that fuzzy logic combined with machine learning technology can better characterize the nonlinear mapping relationship between data, and explore more potential relationships between parameters to improve the prediction effect.

Keywords: permeability prediction, fuzzy logic, machine learning, support vector machine, LSTM neural network.

Wei Guo✉, Yuan Cai, Weiwei Dong, Ning Wang, Hairong Zhang, Yun Mo

Information and Communication Branch, Hainan Power Grid Company, Haikou, China.

guanping618@126.com

Research on the Management Method of New Integrated Energy System Considering Carbon Emission Reduction

Low carbon and environmental protection are becoming increasingly important in the development and utilization of oil and gas resources, so it is crucial to effectively improve the efficiency of low-carbon management. Aiming at the operational requirements of the integrated energy system containing a large number of uncertain resources under the low-carbonization goal, this paper establishes a novel management method. Firstly, a low-carbonization synergistic operation model of carbon capture-P2G is constructed to promote the efficient interaction of the integrated energy system through the multimodal synergistic utilization of carbon cycle and hydrogen energy, and an optimal probabilistic energy flow model of the integrated energy system is established based on it. Then, to address the problem that it is difficult to balance the computational accuracy and solving efficiency of the existing solving methods, this paper proposes a new stochastic response surface (SRS) algorithm, which adopts Taylor series expansion to decouple and simplify the cross terms in the chaotic polynomials, so as to overcome the defects of the SRS that is difficult to deal with high-dimensional stochastic variables. Finally, the accuracy and adaptability of the proposed model and method are verified based on the test systems.

Keywords: *new power system, integrated energy, carbon emission reduction, renewable energy.*

Wang Shuai¹✉, **Li Yuanjun**², **Feng Guang**³, **Wang Jianguang**⁴, **Hu Po**⁵, **Xie Chao**⁶,

Zhang Liang⁷, **Wang Hui**⁷

¹ Yanchang Gas Field Gas Production Plant 4 of Shaanxi Yanchang Petroleum (Group) Co., Ltd., Yan'an City, Shaanxi Province, China;

² The No.1 Gas Production Plant, PetroChina Changqing Oilfield Company, Xi'an, Shaanxi, China;

³ Tazhong Oil and Gas Production Management Area Of PetroChina Tarim Oilfield Company, Xinjiang Korla City, China;

⁴ Tenth Oil Production Plant Of PetroChina Changqing Oilfield Company Branch Gansu Qingyang, China;

⁵ Yumen Oilfield Huanqing Branch Of PetroChina, Gansu Qingyang, China;

⁶ Tongyuan Petroleum Technology Group Co., Ltd., Xi'an, Shaanxi, China;

⁷ PetroChina Qinghai Oilfield Company Oil Production Plant 2, Mangya City, Haixi Prefecture, Qinghai, China

shengan92932055@163.com

Experimental Study on CO₂ Injection to Enhance Recovery

and Its Storage Characteristics in Low Permeability Gas Reservoirs

This study explores the effectiveness of CO₂ injection for enhancing methane (CH₄) recovery and its storage characteristics in low permeability gas reservoirs. Conducted under controlled conditions of 90°C and 10 MPa, experiments employed a CO₂ injection rate of 0.4 mL/min to assess displacement efficiency between dry cores and cores saturated with bound water. The results indicate that the presence of bound water significantly delays CO₂ breakthrough by approximately 0.15 PV compared to

dry cores, leading to a longer transition zone as CO₂ first dissolves in the bound water before effectively displacing CH₄. In wet cores, initial effective displacement of CO₂ is minimal, resulting in a lag in CH₄ recovery rates. However, the final CH₄ recovery rate in wet cores is slightly higher than that in dry cores due to the ability of bound water to occupy smaller pores, facilitating the displacement process. Additionally, CO₂ storage efficiency is evaluated through retention rates and storage ratios. The presence of bound water enhances CO₂ retention, significantly increasing retention rates during injection. The dissolved CO₂ in formation water accounts for a substantial portion of the pore volume, indicating improved solubility at higher pressures. In conclusion, this research demonstrates that CO₂ injection not only improves CH₄ recovery but also serves as a viable method for geological CO₂ storage in gas reservoirs, with recovery rates ranging from 88.37% to 96.29% and breakthrough times between 0.62 PV and 0.88 PV.

Keywords: *gas recovery, CO₂ injection, displacement efficiency, CO₂ storage, gas reservoirs.*

Jun Ni¹✉, Chengjun Wang², Hailong Dang¹, Hongwei Jing³

¹ Shaanxi Yanchang Petroleum(Group) Co.,LTD. Yan'an, Shaanxi, China;

² Xi'an Shiyou University, Xi'an, Shaanxi, China;

³ China University of Petroleum, Beijing, China.

njzzy134@126.com

Influence of Asphaltene Precipitation during CCUS Processes

in Oil Reservoirs on Enhancing Recovery Rates

Reservoirs are ideal locations for CO₂ sequestration. During the development of oilfields, CO₂ is injected, where a portion of the gas dissolves or diffuses into the crude oil and formation water, while another portion reacts with the rock, precipitating within the reservoir. The study of the interactions between CO₂ and reservoir fluids (formation water and crude oil) during the CO₂ flooding process, as well as the resulting precipitation patterns and their impact on reservoir properties and recovery rates, is of significant importance. This paper analyzes the results of a core displacement study on the interactions among CO₂, formation water, and rock, revealing the mechanisms by which carbon dioxide interacts with highly saline formation water and crude oil. It advances the development of CO₂ flooding theory and numerical simulation methods, enhances the understanding of the applicability and development patterns of CO₂ enhanced oil recovery techniques in low permeability reservoirs, and provides strong guidance for the field application of CO₂ flooding technology in low permeability reservoirs containing highly saline formation water. The quantitative characterization is beneficial for informing the development strategies for CCUS in reservoirs.

Keywords: *CCUS, water alternating gas, flooding experiment, asphaltene, reservoir properties.*

Wei Wu¹✉, Nan Zhou¹, Xiaohua Zhu¹, Mingwang Bai²

¹ Jilin Oilfield Company of China National Petroleum Corporation, Jilin, 138000, China;

² College of Oil and Gas Engineering, Liaoning Petrochemical University, Fushun, Liaoning, 113001, China.

wu-wei@petrochina.com.cn

Research on the Rock Pore Structure and Porosity-Permeability Characteristics of Oilfield Saline Aquifer CCS

CCS (Carbon Capture and Geological Storage) is the single most likely technology to achieve industrialized emission reduction. CO₂ geological storage has undergone experimental demonstrations in many countries and is in the industrialization preparation stage. However, in terms of the application in oilfields, the two core issues of "injectivity" and "safety" have not been fundamentally resolved. In view of this, this paper focuses on exploring the influencing factors of the interaction between carbon dioxide - formation water - rock under different formation conditions in oilfields, as well as the injectivity of carbon dioxide in oilfield reservoirs, and the variation laws of reservoir physical properties after carbon dioxide injection into oilfield reservoirs. The aim is to provide theoretical support and practical guidance for the application of CCS technology in oilfields to achieve emission reduction and enhanced oil recovery.

Keywords: CO₂ geological storage, injectivity, pore structure, displacement experiment, water-gas alternation.

Mingwei Ren^{1,2}, Yunbo Chen¹, Kewei Gao², Zheng Wang³, Qian Ma¹, Lianying Liu³

¹ State Key Laboratory of Advanced Forming Technology and Equipment, Beijing National Innovation Institute of lightweight Ltd., Beijing, China;

² School of Materials Science and Engineering, University of Science and Technology Beijing, Beijing, China;

³ College of Materials Science and Engineering, Beijing University of Chemical Technology, Beijing, China.

1270004677@qq.com

In-situ Growing Polymer Particles on Carbon Fiber for Improving Interfacial Properties of Epoxy Composites

To greatly improve the interfacial adhesion between carbon fiber and epoxy matrix, herein, we report a rapid and efficient method of growing polymer microspheres on carbon fiber (CF) by in-situ thiol-isocyanate click dispersion polymerization with the presence of polyvinylpyrrolidone (PVP). The surface morphology observations of modified CF by scanning electron microscopy (SEM) indicated an obvious increase in surface roughness. Fourier-transform infrared (FT-IR) spectra, X-ray photoelectron spectra (XPS) and thermogravimetric analyses (TGA) confirmed the introduction of functional groups on CF. Dynamic contact angle and surface tension measurements displayed the enhancements of wettability and

surface energy of CF. Compared to the untreated carbon fiber, the transverse fiber bundle tensile strength (TFBT) and interfacial shear strength (IFSS) of modified carbon fiber/epoxy composites increased 150.97% and 68.47%. Simultaneously, the single fiber tensile strength of modified CF also showed an increase by 9.65%. Finally, schematic model of interphase reinforcing mechanism was analyzed.

**Yun Jianbing¹✉, Yuan Kaitao², Li Changyan³, Luo Xin³, Wang Yaya³,
Yang Mingkun³, Zhou Xiao⁴, Wang Jing⁵**

¹ Exploration Department, PetroChina Daqing Oilfield Company, Daqing, Heilongjiang, China;

² Yanchang Oilfield Co., Ltd. Dingbian Oil Production Plant, Yulin City, China;

³ Qinghai Oilfield Branch of PetroChina, Qinghai Mangya Haixi Mongolian and Tibetan Autonomous Prefecture, China;

⁴. Xi'an Alberta Resource & Environment Analysis and Testing Technology Co., Ltd., Xi'an, China;

⁵ China Petroleum Changqing Oilfield Branch Second Oil Production Plant, Qingyang City, Gansu, China;

kfsfff@163.com

Analysis of Gas Reservoir Types and Main Controlling Factors of Enrichment and High Yield in Sichuan Basin

The formation of large and medium-sized gas fields in Sichuan basin is closely related to many main controlling factors, which have a significant control effect on oil and gas accumulation. Therefore, the analysis of gas reservoir types and main controlling factors of enrichment and high yield in Sichuan basin is put forward. Set up the basic framework of structural, stratigraphic, lithologic and fractured gas reservoirs, and analyze the geological background; The characteristics and main controlling factors of four gas reservoir types are explored, and on this basis, the concrete embodiment of sediment structure in the upper gas reservoir types in Sichuan Basin is analyzed, and the controlling effects of reservoir, structure and fracture are studied in the gentle fold area in central Sichuan. This paper analyzes the natural gas enrichment and high-yield models in western Sichuan thrust belt, northern Sichuan low-level fold belt and Xujiahe Formation. The experimental results show that this method can improve the analysis efficiency, effectively reduce the influence of data error and subjectivity on the analysis results, and the safety factor is high. With the passage of time, the permeability of gas reservoirs in different regions has decreased significantly.

Keywords: Sichuan basin, gas reservoir type, enrichment and high yield, main control factor analysis.

**Bai Xingjia¹, Feng Rong², Zhang Zhehao³, Xu Jing⁴, Wang Junjun⁵, Bai Yiyuan⁵,
Yang Wenlai⁶, Li Yuanjun⁷**

¹ Shaanxi Yanchang Petroleum (Group) Yanchang Gas Field Gas Production Plant 4, Yan'an City, Shaanxi Province, China;

² Shaanxi Geological Survey Institute, Xi'an, Shaanxi, China;

³ Research Institute, China National Logging Corporation, Xi'an, Shaanxi, China;

⁴ Petroleum Exploration and Development Department of Shaanxi Yanchang Petroleum (Group) Gas Field Company, Yan'an, Shaanxi, China;

⁵ Department of Geology, Northwest University, Xi'an, Shaanxi, China;

⁶ Linfen Branch of PetroChina Coalbed Methane Co., Ltd., Shanxi, Linfen, China;

⁷ The No.1 Gas Production Plant, PetroChina Changqing Oilfield Company, Xi'an, Shaanxi, China

Study on Gas Production Mechanism of Foam Drainage and Optimization of Technological Parameters

To enhance the recovery factor of gas fields, foam drainage is an ideal method, particularly when the gas well's production is not too low, the natural gas flow rate is sufficient, and the liquid accumulation is moderate. This study investigated the liquid carrying capacity of different foaming agents in salt solutions with varying temperatures and salinities through dynamic foam tests. By analyzing the gas quality, water quality, and process characteristics of low-yield gas wells, a new type of foaming agent was developed, which is resistant to high mineralization, oil, and methanol. The injection process parameters were then optimized to ensure effective performance. The results showed that the newly developed foaming agent could foam and carry liquid effectively under conditions with water mineralization of less than 150,000 mg/L and methanol content of less than 50%. Field tests of foam drainage gas production were conducted on-site, with significant improvements observed. During the test, the average differential pressure of the oil casing in a single well decreased by 2.9 MPa, while the average daily liquid production increased from 0.37 m³ to 0.9 m³, indicating a good drainage effect. As a result, the gas recovery rate of the well was significantly improved, with the comprehensive gas recovery rate increasing by 28.14% during the experimental period compared to the same period in previous operations. For the foam drainage process, the preferred injection method involved using an alcohol injection pump to add the foaming agent, combined with a pry-mounted foam discharge dosing truck and a foam discharge rod through a dosing cylinder.

Keywords: gas field, foam drainage, mineralization, gas recovery, carry liquid.

Liu Ting¹✉, Zhang Zheng¹, Dongye Shengfu¹, Zhao Jinlin¹, Zhang Fashi¹, Yu Yao²

¹ No.2 Oil Production Plant of PetroChina Changqing Oilfield Branch, Qingyang, Gansu, China;

² No.7 Oil Production Plant of PetroChina Changqing Oilfield Branch, Qingyang, Gansu, China
280515144@qq.com

Evaluation of Chemical Properties of Microemulsion and Experimental Study of Oil Displacement Mechanism

Polymer macromolecules are difficult to enter low permeability reservoirs due to the characteristics of narrow pore throat, serious reservoir heterogeneity and high injection pressure. At present, low permeability oil fields are mainly developed by water drive, and the recovery rate is low. Therefore, the microemulsion flooding technology of low permeability reservoir is studied in order to develop low permeability oilfield reasonably and efficiently. The results show that the interfacial tension of the three microemulsions can reach an ultra-low level, and the interfacial tension of the betaine microemulsion is the lowest, which is 0.0026mN/m. The three microemulsions have particle size peaks between 0.08 μ m and 0.1 μ m, and can easily pass through low-permeability core pores. The microemulsion viscosity is 7.2,8.5,7.4 mPa·s,respectively, which has a good ability to reduce the water-oil mobility ratio. In terms of solubilization capacity, MSDDS microemulsion had the strongest solubilization capacity, reaching 11.7mL/g, while TW-20 and ABSC-14 microemulsion solubilization parameters were 9.5mL/g and 10.6mL/g, respectively. When the temperature is higher than the turbidity point of nonionic surfactants, the microemulsions appear stratified turbidity. Due to its ultra-low interfacial tension and better solubilization parameters, betaine microemulsion improved the recovery rate by 16.45%.

Key words: microemulsion, phase transformation mechanism, performance evaluation, application effect.

Jiang Jun

School of Economics and Management, Northeast Petroleum University, Daqing, China.

jiangdan6551836@163.com

Chemical Performance Evaluation and Economic Benefit Analysis of Corrosion Resistant Coatings for Oil and Gas Pipelines

In order to improve the corrosion resistance of oil and gas pipelines, this study conducted a chemical performance evaluation and economic benefit analysis of corrosion-resistant coatings for oil and gas pipelines. Prepare corrosion-resistant coatings for oil and gas pipelines, apply them onto steel plate specimens, prepare samples, conduct tests on heat resistance, electrochemical impedance, etc., and complete the chemical performance evaluation of the coatings. Based on cost analysis, conduct an economic benefit study on the corrosion-resistant coating. The experimental results show that the corrosion-resistant coating can maintain the stability of the structure in high temperature environments, with a high impedance value. It can effectively block the corrosion of the substrate by electrolyte solutions, significantly reduce the corrosion rate, and protect pipeline steel plates from corrosion damage. At the level of economic benefit analysis, taking into account the cost of coating preparation, construction, and maintenance saved due to reduced corrosion during long-term use, although the initial investment of this corrosion-resistant coating was relatively high, its excellent anti-corrosion performance effectively reduced pipeline maintenance costs and replacement frequency, demonstrating significant economic benefits in long-term operation. Meanwhile, its excellent weather resistance and durability reduce the downtime losses caused by frequent maintenance, further enhancing the overall economic benefits.

Keywords: oil and gas pipelines, corrosion resistance, coating, chemical properties, economic performance.

CORRECTION

To the article “A Preview of the Subsea Christmas Tree Installation Procedure,” Vol. 60, No. 5, pp. 1289–1296, November, 2024.

The authors of the article should read: **Xinjing Xu¹, Jinfeng Ji¹, Li Li²✉, Xiang Xu¹**.

¹ Hainan Longpan Oilfield Technology Co. LTD; ² China University of Petroleum-Beijing

Xinjing Xu¹, Jinfeng Ji¹, Li Li² ✉, Xiang Xu¹

¹ Hainan Longpan Oilfield Technology Co. LTD, China;

² China University of Petroleum-Beijing.

LL1974922204@163.com

A Preview of the Subsea Christmas Tree Installation Procedure

In the process of deep-water gas field development, the deep-water production system plays a key role, and the deep-water production system has been widely used in the development of the world's offshore gas fields. In this paper, the author uses the X gas field as an example to introduce the subsea christmas tree installation procedure and the reliability of subsea tree production stage by using fault tree analysis (FTA). The installation procedure of the subsea christmas tree is divided into three steps: preparatory work before going in; pulling out the retracted part of the protective leg; using the tree running tool (LTRT) to install the subsea christmas tree. In this paper, the author introduces the installation procedure of subsea christmas tree detailedly, which is important in ensuring the independent and efficient development of offshore gas fields. According to the FTA analysis of throttle module, wellhead connector module and tubing hanger module, the average failure probability of subsea christmas tree production stage is 25.82 times every 106 hours, and the average failure interval is 4.42 years.

Keywords: offshore gas field, subsea christmas tree, installation procedures, tree run tool (LTRT).